

### Description

Quick recovery high density foam pad incorporating a single sided low tack peel-able acrylic adhesive which leaves no adhesive residue on removal.

### **UV and Temperature Resistant**

### Technical Data

<b>Colour</b>	Blue
<b>Size</b>	24mm x 19mm
<b>Thickness</b>	4mm
<b>Density PVC Foam</b>	275KGM/M3
<b>Shore Hardness (00)</b>	65-90
<b>Compression</b>	10% (DIN 53572)
<b>UV Exposure</b>	Good
<b>Temperature Resistance</b>	-50 +60 Centigrade (BS2571)
<b>Adhesive</b>	7-10gsm peelable acrylic adhesive pressure sensitive
<b>Presentation</b>	Reels of 10,000 pads

### Applications

Protection pads designed for the separation and protection of flat glass, sealed units and automotive glass in storage and transit.

Suitable as a protective barrier on glass, metal, plastic and PVC-u surfaces.

### Storage

This product must be stored in its original packaging in a clean, dry, well ventilated area.

Application at low temperatures may increase the possibility of condensation on the surface causing a reduction in the final bond strength.

### Shelf Life

The shelf life of the product once in use depends on the conditions under which the glass is stored.

Additional heat and humidity will affect the ageing process of the PVC foam but not the adhesive itself.

If stored in its original packaging in a clean, dry, well ventilated area the shelf life would be a minimum of 6 months.

### Notes

All technical data is based on average values. By nature of its manufacture, all foam specifications can vary by 10%.

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable and should not be construed in any manner as warranties expressed or implied.

The user should determine the suitability of the product for the application and we strongly recommend testing of this product under individual application conditions.

The user assumes all risks and liability whatsoever in connection herewith.